

ZS500B/ZS500B-1/ZS500B-2

万千纵横，一路领先。
Proved to be the leader in the field!



ZS500B/ZS500B-1/ZS500B-2

项目	机型	ZS500B	ZS500B-1	ZS500B-2
微耕机	机体尺寸(mm)		1380×650×970	
	净重/毛重(kg)		45/60	
	耕幅(mm)		800-1200	
	耕深(mm)		150-300	
	变速档数	0, 1, 2档	1档	0, 1, -1档
	主要离合传动方式		皮带传动	
	传动箱机油容量(L)		0.95	
	发动机型号		ZS168FB	
	缸径×行程(mm)		68×54	
	排量(mL)		194	
发动机	压缩比		8.5: 1	
	最大输出功率 HP(kw)/rpm		6.5 (4.8) /3600	
	额定功率 HP(kw) /rpm		5.7 (4.2) /3600	
	最大扭矩 M.m/rmp		13.2/2500	
	燃油容积(L)		3.6	
	机油容积(L)		0.6	
	最低油耗(g/KW.h)		313	
	空滤器型号		半干、油浴、泡沫滤芯	
	点火方式		晶体管点火	
	发动机形式		OHV25° 倾斜、单缸、四冲程	
包装	包装箱尺寸(长×宽×高)(mm)		805X755X715	
	20英尺集装箱装货数量(台)		63	
	配置	有前轮和挡泥板	无前轮和挡泥板	有前轮和挡泥板

Type	Item	ZS500B	ZS500B-1	ZS500B-2
Tillage machine	Body size(mm)		1380×650×970	
	Net weight/Gross weight(kg)		45/60	
	Tilling scope(mm)		800-1200	
	Tilling depth(mm)		150-300	
	Gear shifting	0, 1, 2	1	0, 1, -1
	Driving model		Belt	
	Transmission oil capacity(L)		0.95	
	Engine model		ZS168FB	
	Bore×stroke(mm)		68×54	
	Displacement(ml)		194	
Engine	Compression ratio		8.5: 1	
	Max. Output(hp.kw/rpm)		6.5 (4.8) /3600	
	Rated power(hp.kw/rmp)		5.7 (4.2) /3600	
	Max.torque(M.m/rmp)		13.2/2500	
	Fuel capacity(L)		3.6	
	Oil Capacity(L)		0.6	
	Min. Fuel Consumption(g/kw.h)		313	
	Air cleaner model		Semi-dry, Oil bath, Dual, Silent, Cyclone	
	Ignition model		Transistor magneto	
	Engine model		OHV25°, inclined, 1-cylinder, 4-stroke	
Dimension	Package dimensions(mm)		805X755X715	
	20FT cont load (set)		63	
	Features	With front wheel and fender	Without front wheel and fender	With front wheel and fender